



Fig. 17 Final form of the SMA actuator.

6. CONCLUSIONS

Actuation of the specified robotic joints proved to be successful by replacing the already existing DC motor with a SMA actuator. The actuator provided less power consumption when compared to the DC motor by 79%. Also with the absence of power transmission technique represented by the toothed belts and gears, power loss due to friction factor has no noticeable effect besides that of the small value due to the presence of pulleys. Although reducing the size of the original prototype by 57% still did not provide a competitive size compared to compactness of the DC motor, it provided a lighter actuator. Additionally, the SMA actuator can be further reduced to be without a wooden base and be placed inside robot's members as pulleys and rods to be mounted inside the arm, taking quite a small space and gaining the advantage over the DC motor. The SMA provided no audial noise during contraction or elongation. The bandwidth of the actuator is considered to be reasonable with a contraction occurring in less than a second and an elongation taking less than 3 seconds; a value achieved by applying forced air cooling. The main challenging aspect about SMA actuators is providing a method of control due to their non-linearity and hysteresis during the contraction and elongation. A model was successfully created to capture the behaviour of the hysteresis of the SMA, this was done through Hammerstein-Weiner model with a curve fit of 99%. Thus, SMAs are considered extremely beneficial materials when it comes to actuation applications of robotic joints. Their distinctive properties place them a head competitor with conventional actuators. Of the various types of SMAs for robotic joint actuators, NiTi proved to be the best alloy.

REFERENCES

- Aaltio, I., Heczko, O., Soderberg, O. and Hannula, S. (2008). "Magnetically Controlled Shape Memory Alloys", In M. Schwartz (Ed.) *Smart Materials*, Boca Raton, CRC Press, pp. 20.1-20.8.
- Ahn, K. K., and Kha, N. B. (2006). "Improvement of the Performance of Hysteresis Compensation in SMA Actuators by Using Inverse Preisach Model in Closed—Loop Control System". *Journal of Mechanical Science and Technology*, **20**(5), p. 634.

- Ahn, K. K., and Kha, N. B. (2007). "Internal Model Control for Shape Memory Alloy Actuators Using Fuzzy Based Preisach Model". *Sensors and Actuators A: Physical*, **136**(2), pp. 730-741.
- Andrianesis, K. and Tzes, A. (2015). "Development and Control of a Multifunctional Prosthetic Hand with Shape Memory Alloy Actuators", *Journal of Intelligent and Robotic Systems*, **78**(2), pp. 257-289.
- Bellouard, Y. (2008). "SMAs in Micro- and Nanoscale Engineering Applications", In M. Schwartz (Ed.) *Smart Materials*, Boca Raton, CRC Press, pp. 20.8-20.17.
- Caballero, A. F. Copaci, D. S. Rojas, D. B. Peciña, Á. V. and Lorente, L. M. (2015). "High-Displacement Flexible Shape Memory Alloy Actuator for Soft Wearable Robots", *Robotics and Autonomous Systems*, vol. **73**, pp. 91-101.
- Callister, W. D. and Rethwisch, D. G. (2014). *Materials Science and Engineering*, New Jersey: John Wiley & Sons, Inc.
- Doroftei, I., & Stirbu, B. (2014). "Application of Ni-Ti Shape Memory Alloy Actuators in a Walking Micro-Robot", *Mechanics*, **20**(1), pp. 70-79.
- Dynalloy (2017). "Technical Characteristics of Felxinol Actuator Wires", Available: <http://www.dynalloy.com/pdfs/TCF1140.pdf>
- Fathi, A., and Mozaffari, A. (2013). "Identification of a Dynamic Model for Shape Memory Alloy Actuator Using Hammerstein-Wiener Gray Box and Mutable Smart Bee Algorithm". *International Journal of Intelligent Computing and Cybernetics*, **6**(4), pp. 328-357.
- MathWorks (2017). Identifying Hammerstein-Wiener Models. Retrieved from <https://www.mathworks.com/help/ident/ug/identifying-hammerstein-wiener-models.html>
- Mavroidis, C., Pfeiffer, C., & Mosley, M. (1999). "Conventional Actuators, Shape Memory Alloys, and Electrorheological Fluids", In Y. Bar-Cohen (Ed.) *Automation, Miniature Robotics, and Sensors for Nondestructive Testing and Evaluation*, **4**, p. 189.
- Pittman (2017). DC054B-4 (14204) Brush DC Motor. Retrieved from <http://www.pittman-motors.com/Brush-DC-Motors/14204-Brush-DC-Motor.aspx>
- Van Humbeeck, J. (2008). "Shape Memory Alloys", In M. Schwartz (Ed.) *Smart Materials*, Boca Raton, CRC Press, pp. 20.28-20.36.
- Zakerzadeh, M. R., Sayyaadi, H., and Zanjani, M. V. (2011). "Characterizing Hysteresis Nonlinearity Behavior of SMA Actuators by Krasnosel'skii-Pokrovskii Model". *Applied Mathematics*, **1**(1), pp. 28-38.