





















## REFERENCES

- Abrahamson NA, Bolt BA, Darragh RB, Penzien J (1987), "The SMART 1 accelerograph Array (1980-1987): A Review", *Earthquake Spectra*, 3:263-287.
- Berteussen KA (1974), "NORSAR location calibrations and time delay correction", in *NORSAR Semiannual Technical Summary. 1 October 1973 to 31 March 1974. Scientific Report 2-73/74*, Kjeller, Norway, 41.
- Bouchon M and Aki K (1982), "Strain, tilt and rotation associated with strong ground motion in the vicinity of earthquake faults", *Bulletin of the Seismological Society of America*, 72:1717-1738.
- Capon J (1969), "High-resolution frequency- wavenumber spectrum analysis", *Proc. IEEE*, 57:1408-1418.
- Chen YT (1974), "Seismic Waves in Multilayered Elastic Half-space", *Chinese Journal of Geophysics*, 53(1):20-43. (in Chinese)
- Chung JK (2007), "Estimation of ground strain using accelerograms recorded by two dense seismic arrays at Lotung, Taiwan", *Terrestrial Atmospheric and Oceanic Sciences*, 18:715-737.
- Davies D, Kelly EJ and Filson JR (1971), "The VESPA process for the analysis of seismic signals", *Nature*, 232:8-13.
- Ding HP and Jin X (2000), "Simulation of transfer function for seismic response of soil layers", *World Information on Earthquake Engineering*, 16:35-41(in Chinese).
- Geologic Surveyed Data of CWB Strong Motion Stations, <http://geo.ncree.org.tw/>
- Ghayamghamian MR and Nouri GR (2007), "On the characteristics of ground motion rotational components using Chiba dense array data", *Earthquake Engineering and Structural Dynamics*, 36:1407-1429.
- Hao H. (1996), "Characteristics of torsional ground motion", *Earthquake Engineering and Structural Dynamics*, 25:599-610.
- Hart GC, DiJulio RM and Lew M (1975), "Torsional response of high-rise buildings", *ASCE, J. Struct. Division* 101:397-415.
- Haskell NA (1953), "The dispersion of surface waves on multilayered media", *Bulletion of the Seismological Society of America*, 43(1):17-34.
- International Conference of Building Officials (1997), *Uniform Building Code*, Chapter 16, California.
- Li HN, Sun LY and Wang SY (2004), "Improved approach for obtaining rotational components of seismic motion", *Nuclear Engineering and Design*, 232:131-137
- Li HN and Wu XX, (2004) "Simplified formulate of torsional seismic actions for base-isolated eccentric structures," *Journal of the Harbin Institute of Technology*, vol. 26, no. 1, pp. 52-54. (in Chinese)
- Igel H, Cochard A, Wassermann J, Flaws A, Schreiber, U, Velikoseltsev A and Dinh N (2007), " Broad-band observations of earthquake-induced rotational ground motions", *Geophys. J. Int.*, 168:182-196.
- Kosuke H and Ping JS (2005), "Directivity and apparent velocity of the coseismic ionospheric disturbances observed with a dense GPS array", *Earth and Planetary Science Letters*, 236:845-855.
- Kuo CH, Wen KL, Hsieh HH, Chang TM, Lin CM and Chen CT (2011), Evaluating empirical regression equations for Vs and estimating Vs30 in northeastern Taiwan,

- Soil Dynamics and Earthquake Engineering, 31: 431-439.
- KvÈrna T and Doornbos DJ (1986), "An integrated approach to slowness analysis with arrays and three-component stations", in NORSAR Semiannual Technical Summary, 1 October 1985 to 31 March 1986, Scientific Report 2-85/86, NORSAR, Kjeller, Norway, 60-69.
- KvÈrna T and Ringdal F (1986), "Stability of various f-k estimation techniques. in NORSAR Semiannual Technical Summary, 1 April 1986 to 30 September 1986, Scientific Report 1-86/87, NORSAR, Kjeller, Norway, 29-40.
- Lacoss RT, Kelly EJ and Toksoz MN (1969), "Estimation of seismic noise structure using array", *Geophysics*, 29:21-38.
- Lee and Tsai (2008), Mapping Vs30 in Taiwan, *Terr. Atmos. Ocean. Sci.*, 19(6): 671-682.
- Luco JE (1976), "Torsional response of structures to obliquely incident seismic SH waves", *Earthquake Engineering and Structural Dynamics*, 4:207-219.
- Nathan ND and MacKenzie JR (1975), "Rotational components of earthquake motions", *Can. J. Civil Eng.*, 2:430-436.
- Newmark NM (1969), "Torsion in symmetrical buildings", *Proc. Fourth World Conference on Earthquake Eng.*, Vol. II, Santiago, Chile, 19-32.
- Nigbor RL (1994), "Six-degree of freedom ground motion measurement", *Bulletion of the Seismological Society of America*, 84: 1665–1669.
- Rutenberg A and Heidebrecht AC (1985), "Rotational ground motion and seismic codes", *Can. J. Civil Eng.*, 12:583-592.
- Spudich P, Steck LK, Hellweg M, Fletcher J and Baker LM (1995), "Transient stresses at Parkfield, California, produced by the M7.4 Landers earthquake of June 28, 1992: observations from the UPSAR dense seismograph array", *J. Geophys. Res.*, 100: 675-690.
- Stedman GE, Li Z and Bilger HR. (1995), "Side band analysis and seismic detection in a large ring laser", *Applied Optics*, 34:7390–7396.
- Suryanto W, Igel H, Wassermann J, Cochard A, Schuberth B, Vollmer D, Scherbaum F, Schreiber U and Velikoseltsev A (2006), "First comparison of array-derived rotational ground motions with direct ring laser measurements", *Bulletion of the Seismological Society of America*, 96: 2059-2071.
- Takeo M (1998), "Ground rotational motions recorded in the near-source region of earthquakes", *Geophys. Res. Let.*, 25:789-792.
- Satoh T, Kawase H, Iwata T, Higashi S, Sato T, Irikura K, and Huang HC (2001), "S-wave velocity structure of the Taichung Basin, Taiwan, estimate from array and single-station records of microtremors", *Bulletin of the Seismological Society of America*, 91:1267-1282.
- Trifunac MD (2006), "Effects of torsional and rocking excitations on the response of structures, in *Earthquake Source Asymmetry, Structural Media and Rotation Effects*", R. Teisseyre, et al., editors, Springer Verlag, Heidelberg, 569-582.
- Vladimir MG (2005), "Effect of tilt on strong motion data processing", *Soil Dynamics and Earthquake Engineering*, 25:197-204.
- Wen KL and Yeh YT (1984). Seismic velocity structure beneath the SMART1 array, *Bull. Inst. Earth Sci., Academia Sinica*, 4:51-72.